



Schroeder Torsion Bars



spring rates 1 1/8" x 26" bars hollow tubular effective length 20"

ARM LENGTHS

8 8.5 9 9.5 10 10.5 11 11.5 12 12.5 13 13.5 14 14.5 15 15.5 16

DIAMETER

0.9	568.2	503.3	448.9	402.9	363.6	329.8	300.5	275	252.5	232.7	215.2	199.5	185.5	173	161.6	151.4	142
0.925	638.8	565.8	504.7	453	408.8	370.8	337.9	309.1	283.9	261.6	241.9	224.3	208.6	194.4	181.7	170.2	159.7
0.95	713.7	632.2	563.9	506.1	456.7	414.3	377.5	345.4	317.2	292.3	270.3	250.6	233	217.2	203	190.1	178.4
0.975	793	702.5	626.6	562.4	507.5	460.4	419.5	383.8	352.5	324.8	300.3	278.5	258.9	241.4	225.6	211.3	198.3
1	877.1	776.9	693	622	561.3	509.1	463.9	424.4	389.8	359.3	332.1	308	286.4	267	249.5	233.6	219.3
1.025	966	855.7	763.2	685	618.2	560.7	510.9	467.5	429.3	395.7	365.8	339.2	315.4	294	274.8	257.3	241.5
1.05	1060	938.9	837.5	751.6	678.3	615.3	560.6	512.9	471.1	434.1	401.4	372.2	346.1	322.6	301.5	282.3	265

www.Schroedertorsionbars.com

Burbank, Ca.

www.Schroedersteering.com

Phone 818-565-1133