



# Schroeder Torsion Bars



spring rates 1 1/8" x 29" bars hollow tubular effective length 23"

## ARM LENGTHS

8 8.5 9 9.5 10 10.5 11 11.5 12 12.5 13 13.5 14 14.5 15 15.5 16

## DIAMETER

0.875	436.3	386.5	344.8	309.4	279.2	253.3	230.8	211.2	193.9	178.7	165.2	153.2	142.5	132.8	124.1	116.2	109.1
0.9	494.1	437.7	390.4	350.4	316.2	286.8	261.3	239.1	219.6	202.4	187.1	173.5	161.3	150.4	140.5	131.6	123.5
0.925	555.4	492	438.9	393.9	355.5	322.4	293.8	268.8	246.9	227.5	210.3	195.1	181.4	169.1	158	148	138.9
0.95	620.6	549.7	490.3	440.1	397.2	360.2	328.2	300.3	275.8	254.2	235	217.9	202.6	188.9	176.5	165.3	155.1
0.975	689.6	610.9	544.9	489	441.3	400.3	364.7	333.7	306.5	282.5	261.1	242.2	225.2	209.9	196.2	183.7	172.4
1	762.7	675.6	602.6	540.8	488.1	442.7	403.4	369.1	339	312.4	288.8	267.8	249	232.2	216.9	203.2	190.7
1.025	840	744.1	663.7	595.7	537.6	487.6	444.3	406.5	373.3	344.1	318.1	295	274.3	255.7	238.9	223.8	210
1.05	921.7	816.4	728.2	653.6	589.9	535	487.5	446	409.6	377.5	349	323.7	300.9	280.6	262.2	245.5	230.4
1.075	1008	892.8	796.3	714.7	645	585.1	533.1	487.7	447.9	412.8	381.7	353.9	329.1	306.8	286.7	268.5	252
1.1	1099	973.3	868.2	779.2	703.2	637.8	581.2	531.7	488.3	450.1	416.1	385.9	358.8	334.5	312.5	292.7	274.7

[www.Schroedertorsionbars.com](http://www.Schroedertorsionbars.com)

Burbank, Ca.

[www.Schroedersteering.com](http://www.Schroedersteering.com)

Phone 818-565-1133