



Schroeder Torsion Bars



spring rates 1 1/8" x 30" bars hollow tubular effective length 23"

ARM LENGTHS

8 8.5 9 9.5 10 10.5 11 11.5 12 12.5 13 13.5 14 14.5 15 15.5 16

DIAMETER

0.875	418.1	370.4	330.4	296.5	267.6	242.7	221.2	202.4	185.8	171.3	158.4	146.8	136.5	127.3	118.9	111.4	104.5
0.9	473.5	419.4	374.1	335.8	303	274.9	250.4	229.1	210.4	193.9	179.3	166.3	154.6	144.1	134.7	126.1	118.4
0.925	532.3	471.5	420.6	377.5	340.7	309	281.5	257.6	236.6	218	201.6	186.9	173.8	162	151.4	141.8	133.1
0.95	594.7	526.8	469.9	421.7	380.6	345.2	314.6	287.8	264.3	243.6	225.2	208.8	194.2	181	169.2	158.4	148.7
0.975	660.9	585.4	522.2	468.6	423	383.6	349.5	319.8	293.7	270.7	250.3	232.1	215.8	201.2	188	176	165.2
1	730.9	647.4	577.5	518.3	467.8	424.3	386.6	353.7	324.8	299.4	276.8	256.7	238.7	222.5	207.9	194.7	182.7
1.015	774.9	686.4	612.2	549.5	495.9	449.8	409.8	375	344.4	317.4	293.4	272.1	253	235.9	220.4	206.4	193.7
1.025	805	713.1	636	570.8	515.2	467.3	425.8	389.6	357.8	329.7	304.8	282.7	262.9	245	229	214.4	201.2
1.035	843.6	747.3	666.5	598.2	539.9	489.7	446.2	408.2	374.9	345.5	319.5	296.2	275.5	256.8	240	224.7	210.9
1.05	883.3	782.4	697.9	626.4	565.3	512.7	467.2	427.4	392.6	361.8	334.5	310.2	288.4	268.9	251.2	235.3	220.8
1.065	924	818.5	730.1	655.3	591.4	536.4	488.7	447.2	410.7	378.5	349.9	324.5	301.7	281.3	262.8	246.1	231
1.075	965.9	855.6	763.2	684.9	618.2	560.7	510.9	467.4	429.3	395.6	365.8	339.2	315.4	294	274.7	257.3	241.5
1.1	1053	932.8	832	746.7	673.9	611.3	557	509.6	468	431.3	398.8	369.8	343.8	320.5	299.5	280.5	263.2

www.Schroedertorsionbars.com

Burbank, Ca.

www.Schroedersteering.com

Phone 818-565-1133