



Schroeder Torsion Bars



spring rates 7/8" x 14.5" bars solid effective length 10.75"

ARM LENGTHS

| | 8 | 8.5 | 9 | 9.5 | 10 | 10.5 | 11 | 11.5 | 12 | 12.5 | 13 | 13.5 | 14 | 14.5 | 15 | 15.5 | 16 |
|----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| DIAMETER | | | | | | | | | | | | | | | | | |
| 0.5 | 102.6 | 90.85 | 81.04 | 72.73 | 65.64 | 59.54 | 54.25 | 49.63 | 45.58 | 42.01 | 38.84 | 36.02 | 33.49 | 31.22 | 29.17 | 27.32 | 25.64 |
| 0.525 | 124.7 | 110.4 | 98.5 | 88.4 | 79.79 | 72.37 | 65.94 | 60.33 | 55.41 | 51.06 | 47.21 | 43.78 | 40.71 | 37.95 | 35.46 | 33.21 | 31.17 |
| 0.55 | 150.2 | 133 | 118.6 | 106.5 | 96.1 | 87.17 | 79.42 | 72.67 | 66.74 | 61.51 | 56.87 | 52.73 | 49.03 | 45.71 | 42.71 | 40 | 37.54 |
| 0.575 | 179.4 | 158.9 | 141.7 | 127.2 | 114.8 | 104.1 | 94.88 | 86.81 | 79.72 | 73.47 | 67.93 | 62.99 | 58.57 | 54.6 | 51.02 | 47.79 | 44.85 |
| 0.6 | 212.7 | 188.4 | 168 | 150.8 | 136.1 | 123.5 | 112.5 | 102.9 | 94.52 | 87.11 | 80.54 | 74.68 | 69.44 | 64.74 | 60.49 | 56.65 | 53.17 |
| 0.625 | 250.4 | 221.8 | 197.8 | 177.6 | 160.3 | 145.4 | 132.4 | 121.2 | 111.3 | 102.6 | 94.82 | 87.93 | 81.76 | 76.22 | 71.22 | 66.7 | 62.6 |
| 0.65 | 292.9 | 259.5 | 231.4 | 207.7 | 187.5 | 170 | 154.9 | 141.8 | 130.2 | 120 | 110.9 | 102.9 | 95.65 | 89.17 | 83.32 | 78.03 | 73.23 |

www.Schroedertorsionbars.com

Burbank, Ca.

www.Schroedersteering.com

Phone 818-565-1133