



Schroeder Racing Products



Cup Front Sway Bar Spring Rates

37 1/2 Long Bars Hollow 1 1/2" 48 Spline Ends

Arm Length Center Distance inches

Diameter	lbs at 1 inch arm travel						
	11	11.5	12	12.5	13	13.5	14
7/8	183	167	154	141	131	121	113
15/16	243	222	204	188	174	161	150
1	316	289	265	244	226	209	195
1 1/16	402	368	338	312	288	267	248
1 1/8	506	463	425	392	362	336	312
1 3/16	628	575	528	486	450	417	388
1 1/4	775	709	651	600	555	515	478
1 5/16	944	863	793	731	676	626	582
1 3/8	1132	1036	951	876	810	751	699
1 7/16	1356	1241	1140	1050	971	900	837
1 1/2	1615	1477	1357	1250	1156	1072	997
1 9/16	1888	1727	1586	1462	1351	1252	1164
1 5/8	2190	2003	1839	1695	1567	1454	1351
1 11/16	2473	2263	2078	1915	1770	1642	1526
1 3/4	2774	2538	2330	2147	1985	1841	1712
1 13/16	3169	2897	2661	2452	2267	2102	1954
1 7/8	3580	3275	3008	2772	2563	2377	2210
1 15/16	4038	3694	3392	3126	2891	2681	2493
2	4560	4172	3832	3531	3264	3027	2815

www.Schroedertorsionbars.com

Burbank, Ca.

www.Schroedersteering.com

Phone 818-565-1133