



Schroeder Racing Products



Cup Front Sway Bar Spring Rates

37 1/2 Long Bars Hollow 1 3/4" 48 Spline Ends

Arm Length Center Distance inches

Diameter	lbs at 1 inch arm travel						
	11	11.5	12	12.5	13	13.5	14
7/8	183	167	154	141	131	121	113
15/16	243	222	204	188	174	161	150
1	316	289	265	244	226	209	195
1 1/16	402	368	338	312	288	267	248
1 1/8	506	463	425	392	362	336	312
1 3/16	628	575	528	486	450	417	388
1 1/4	775	709	651	600	555	515	478
1 5/16	944	863	793	731	676	626	582
1 3/8	1132	1036	951	876	810	751	699
1 7/16	1356	1241	1140	1050	971	900	837
1 1/2	1615	1477	1357	1250	1156	1072	997
1 9/16	1911	1748	1606	1480	1368	1268	1179
1 5/8	2244	2053	1885	1737	1606	1490	1385
1 11/16	2566	2348	2156	1987	1837	1704	1584
1 3/4	2914	2666	2448	2256	2086	1934	1799
1 13/16	3321	3039	2791	2572	2378	2205	2050
1 7/8	3749	3430	3150	2903	2684	2489	2315
1 15/16	4222	3862	3547	3269	3023	2803	2606
2	4760	4355	4000	3686	3408	3160	2938

www.Schroedertorsionbars.com

Burbank, Ca.

www.Schroedersteering.com

Phone 818-565-1133